ED

300W/500W/700W/1000W Portable Power Station, Generator Quick Charge - 10~40°C Discharging Temperature Range

Basic Information

Place of Origin: China
Brand Name: MINKO
Certification: CE, ROHS

Model Number: Portable Power Station-M1000

Minimum Order Quantity: 5 piecesPrice: negotiation

Packaging Details: L210xW85xH52 (mm)
 Delivery Time: 8 -10 working days
 Payment Terms: T/T, Western Union,

MoneyGram,Paypal,Skrill,Transferwise

Supply Ability: 1000000 pieces per month



Product Specification

Rated Power AC: 1000WCapacity: 999WhPower Indicate: LCD Display

• Solar Charging Input: 18-23V/3A(60W Max)

• Wireless Charge Output: 10V

• Discharging Temperature

Range:

14~104°F(-10~40°C)

Housing Material: ABS+PCOperation Humidity: 10%~90%

• Highlight: 700w Rechargeable Portable Power Station,

LCD Rechargeable Portable Power Station, 1000w portable battery powered generator



More Images



Product Description

300W/500W/700W/1000W Portable Power Station, Generator Quick Charge -10~40°C Discharging Temperature Range

Features of Portable Power Station

UL certified vehicle level lithium battery

super inverter technology maximum support 1500W equipment (US standard Japanese standard 120V) and maximum support 2000W equipment (Central Europe Australian-British South African standard 230V)

1000W rated output

full large capacity 1 KWH electricity

modeling IP armor warrior

compared to this product size Mini weight light

Apply to:Home emergency, small household appliances, digital products (such as UAV, mobile phone, computer, notebook,camera, handheld head, car refrigerator, etc.), long-distance self-driving travel, outdoor camping, lighting, picnic, wild fishing,environmental monitoring, geological exploration, car electricity, medical equipment and other scenes.

Product Specification

Product Specification	LOCAL
Rated Power AC	1000W
Capacity	999Wh (22.2V/45A or 3.7V/270000mAh)
Battery type	UL Li-ion
Power Indicate	LCD display
LCD Display	Battery remaining capacity, Battery fault, total output power, Over temperature, input power
DC Input	DC24V/6.25A(150W max,adapter with UL,CCC,CE,PSE,FCC)
DC fully Charging Time	About 7∼8H
Solar Controller Model	MPPT
Solar Charging Input	18-23V/3A(60W max)
Charging Temperature Range	32~104°F(0°C~40°C)
USB Output	Type-C output:PD 60W(5V3A,9V3A,12V3A,15V3A,20V3A)*1
	USB-A output:QC3.0(18W/5V3A,9V2A,12V1.5A)*3(total 54W)
Wireless Charge Output	10W
Cigarret Lighter output	12V/10A(120W)
DC output	12V/5A/DC5521*2(total 120W)
LED light	5W*2(total 10W Max)
	SOS,flashlight
AC Output	Output waveform:pure sinewave
	Output voltage:110V(US/JP) or 220V(EU/UK/AU/CN) (AC output
	voltage and frequency are customized, according to different
	countries and regions.Please refer to the actual product)
	Output frequency: 50/60Hz
	Peak AC output:2000W
	AC continuous output: 1000W
Discharging Temperature Range	14~104°F(-10~40°C)
Product size/Weight	328*221*263mm/about 8.9Kg
Carton Size/Weight	32.5*25*36.5CM/about 11.3Kg/1PCS
Protections	over-charging, short-circuit, low-voltage, over-temperatature and
	over-discharging protection
Color	Oranger+gray,Blue+gray,Red+gray,Green+gray
Housing Material	ABS+PC (fireproofing V0)
Working Temperature	-15~45°C
Operation Humidity	10%~90%
Standard Package Include	1*M1000 portable power supply, 1*150W power supply,1*User
	Manual, ,color box packaging,1*MC4 charging cable, 1*vehicle
	charging cable,1*straps
Warrantly	12 months
	1

9 Protections Strictly Abide By Charging Safety Overcurrect protection

Short-circuit protection
Over discharge protection
Low temperature protection
High temperature protection
Overvoltage protection
Overload protection
Signal interference protection

Overcharge protection



Equipped with Uninterruptible Power Supply (UPS)

with UPS function, protect equipment from damage



Function Panel





More use scenarios



















MINKO (SZ) TECHNOLOGY CO., LIMITED



+8613539872669



yumiko@szminko.com evstationcharger.com



309 West Lake Industrial Zone, Cuishan Road, Dongxiao Street, Luohu District, SZ